UTILIZATION OF SOME FOOD INDUSTRIES BY-PRODUCTS TO PRODUCE HIGH FIBER, HIGH PROTEIN RICE-BASED EXTRUDATES

El-Faham, Sawsan Y.; A. A. Shatta and Kh. M. Youssef

Food Technology Dept., National Research Center, Dokki, Giza, Egypt. Food Technology Dept., Faculty of Agriculture, Suez Canal University, Ismailia, Egypt.

ABSTRACT

Three food industries by-products; barley mash, corn gluten feed and corn gluten meal were used to produce high fiber, high protein rice-based extrudates. Barley mash and corn gluten feed characterized by high fiber (10.41 and 11.34%) and high ash (4.63 and 6.43%) content. While, corn gluten meal characterized by high protein (60.25%) contents. These by-products were added by 5, 10, 20 and 30% in order to enhance the fiber and protein contents in the resultant rice-based extrudates. Effects of adding these ingredients on the expansion ratio (ER), bulk density (BD), water absorption index (WAI), water solubility index (WSI), breaking strength (BS), color, chemical composition, minerals content and sensory evaluation of the resultant extrudates were evaluated. The obtained results indicated that adding barley mash alone or as a mixture with gluten meal, and corn gluten feed decreased the ER, WSI, WAI, BS and L^* values of the products, while increased the BD. Incorporation gluten meal caused increase in ER and b* values of the products. Chemical composition and minerals contents were depending upon the composition of the ingredients and substitution ratios. Sensory evaluation indicated that high fiber; high protein extrudates with acceptable quality could be prepared from barley mash alone or as a mixture with gluten meal, corn gluten feed or meal up to 10%.

Keywords: Extrusion, barley, corn gluten feed, corn gluten meal, functional

properties, sensory evaluation, by-products

INTRUDCTION

High-temperature, short time (HTST) extrusion cooking technology has almost limitless application in the processing of cereal-based products of various blends for food as well as feed. It is an effective method to pre-cook grains and flours. It is applied in many food production processes, such as starch depolymerization, manufacture of snack foods, baby foods, pasta products and textured vegetable protein, where the starchy and proteinaceous raw materials were converted into fabricated products. The major application includes the production of breakfast cereals and snacks (Hakulin et al., 1983; Abbott, 1987; Dziezak, 1989; Jin et al., 1994; Konstance et al., 1998 and Rhee et al., 1999).

Snacks and breakfast cereals are essentially produced from starchy substances such as corn, rice, wheat, oat, which are poor sources of protein, sugars, dietary fiber and minerals. These raw materials can be incorporated into a formulation with many other minor ingredients; such as emulsifiers, fats & oils, sugars, salt, fibers, vitamins, proteins and minerals; to change the chemical, physical, sensory and nutritional properties of the product (Linko et al., 1981; Hsieh et al., 1991, Abd El-Hady et al., 1997, 2000 and Abd El-Hady et al. 2002).

Recently, increasing attention has been directed to incorporated dietary fiber into food (Colonna et al., 1989). There are many medical benefits related to dietary fiber presence in meals; decrease lymphatic absorption of cholesterol, bind bile acids and bile salts in vitro, protect against chemically induced cancer; control glucose levels in blood and reduce the daily insulin dose of diabetics, helping weight reduction and physical gastrointestinal tract disorders (Gordon, 1989 and Stauffer, 1993). Many investigations were carried out to offer consumers good extruded products with the beneficial dietary fiber using complex recipes (Andersson et al., 1981; Bjorck et al., 1984; Lue et al., 1991; Berglund et al., 1994; Jin et al., 1994; Abd El-Hady et al., 2000 and Yaseen et al., 2001).

As most snacks and breakfast cereals are poor sources of protein, which has low nutritional quality, the protein supplementation is needed. Many applications were done to increase the nutritional value of many food snacks using high biological value ingredients in formulated mixtures (Almeida-Dominguez et al., 1990; Saleh, 1996; Abd El-Hady et al., 1997 and

1999).

Now-days, there are very interest to maximize the utilization of food sources and use the food industry by-products in new value-added products. Most of food industry by-products were disposed of, sold for sub-market prices or used for animal feeding. Most of these by-products are rich in fibers, proteins and minerals. So, many recent investigations were done to use these materials to produce high nutritional and special foods. Rice bran, soy fiber, oat fiber, pea fiber, sugar beet fiber, apple pomace, barley husks, orange fiber and potato peels were used to produce high dietary fiber extrudates (Bollinger, 1996; Singh et al., 2000; Abd El-Hady et al., 2000a and Yaseen et al., 2001). Also, Kee et al. (2001) studied the physical properties of extruded snack made of onion pomace; a by-product of onion processing; with corn grits.

Many researchers investigated the extrusion of protein-rich animal or fish by-products. Roseg et al. (1991) discussed the utilization of protein-rich meat fish by-products for manufacture of edible extrudates. Murphy et al (2003) and Obatolu et al (2005) studied the chemical composition and physical properties of extruded snacks containing crab-processing and

crustacean by-products.

Therefore, the aim of the present work is to produce a high fiber, high protein extrudates utilizing some of food industry by-products to increase its nutritional and economical values.

MATERIALS AND METHODS

Materials

1-Barley mash (Malt sprouts); consists of dried sprouts and rootlets produced from malting of barley for beer production rich in crude fiber and ash contents was obtained from El-Ahram Company for Beverage, Giza, Egypt..

2-Corn gluten feed (shelled corn remains after the extraction of the larger portion of starch, gluten and germ from the wet milling manufacture of corn starch and syrup) and corn gluten meal (dried residue from corn after removal of the larger part of the starch and germ and separation of the bran) were obtained from National Company for Maize Products, 10th of Ramadan City, Egypt. Rice and dry skim milk (DSM) were purchased from local market at Ismailia governorate. Rice was ground to get homogenous particles size by using a laboratory mill (Brabender Automat Mill Quandrumat Senior, Germany), then used to prepare different blends.

Methods

1- Extrusion

Four mixtures at levels of 5, 10, 20 and 30% of barley mash, corn gluten feed and meal and mixture of barley mash: corn gluten meal (1: 1) with rice grits were extruded using a Brabender laboratory single-screw extruder (20 DN) with varied barrel temperature (130, 180 and 160 °C for feeding, cooking and die zones, respectively), feed moisture (16%), feeding screw speed (160 rpm), screw compression (4: 1), screw speed (250 rpm) and round die opening (3mm) according to the method described by Abd El-Hady and Habiba (2003). The resultant extrudates were dried at 110 °C for 5 min and were allowed to reach room temperature, then subjected for different analyses. The preferable blends after sensory evaluation were supplemented by adding 1% dry skim milk (DSM) as a standard protein.

2- Physical and functional properties

Expansion ratio (ER), the ratio of the cross-sectional diameter of the extrudate sticks to the die exit diameter, was determined according to Gomez and Aguilera (1984). The bulk density (BD, g /100cm3) was carried out by weighing the quantity required to fill a known volume. Water absorption index (WAI), the amount of gel formed per gram extrudate, and water solubility index (WSI), the fraction of dry sample, which was soluble, were determined as described by Anderson et al. (1969). Breaking strength (BS) was measured by using Brabender Struct-o-graph according to Abd El-Hady et al. (1997). Color attributes of the extrudates were determined by Minolta Color Reader, Mo, CR10, Japan. Where, L*, a*, and b* values were measured after ground the extrudates.

3- Chemical composition

Moisture content, crude protein (N* 5.7), ether extract, crude fiber and ash contents were determined as described in the AOAC (1995). Total carbohydrate contents were calculated by difference. Contents of some minerals (K, Ca, Mg, Fe, Mn and Zn) were determined according to AOAC (1995) by wet ashing and using Atomic Absorption Spectrophotometer Varian AA20 (Cottenie, et al. 1982).

4- Sensory evaluation

The sensory evaluation of the extrudates was carried out by staff members and semi-trained panelists for taste (20), crispness (20), chewiness

(15), odor (15), color (10), pore distribution (10) and surface characteristics (10). The overall acceptability of the samples was calculated, from the total scores of tested attributes and grades were given according to the following scale: excellent (86-100), good (76-85), fair (61-75) and poor (< 60) as described by Kramer and Twigg (1970).

5- Statistical analysis

The analysis of variance (ANOVA) was carried out to test the possibility of significant of treatment effect. LSD as described by Ott (1984) was used to perform all possible pair comparisons between means of different treatments.

RESULTS AND DISCUSSION

1- Chemical composition:

The chemical composition of the ingredients, which used in this work, is shown in Table (1). Uses of food industries by-products, high in fibers and or protein, in food technology may serve as an economical target.

Table (1). Chemical composition (%) of the ingredients (on dry basis).

Ingredients	Moisture	Total carbohydrates	Protein	Crude fiber	Ether extract	Ash
Rice grits	12.8 ^b	89.37ª	8.14 ^e	0.26 ^d	1.79 ^d	0.44 ^e
Barley mash	8.7d	39.82 ^d	36.06°	10.41 ^b		4.63°
Corn gluten feed	11.3°	58.15 ^b	20.15°	11.34ª	3.93°	6.43 ^b
Corn gluten meal	13.7ª	30.09°	60.25 ^a	2.21°	6.15 ^b	1.30 ^d
Dry skim milk (DSM)	5.2e	50.83°	39.04 ^b	-	1.33 ^d	8.80 ^a

Means of triplicates

Calculated by difference

Means having the same letter with each property are not significantly different at $p \le 0.05$

2- Physical and functional properties of extrudates

2.1- Expansion ratio (ER):

The data presented in Table (2) showed that the ER of the produced extrudates significantly decreased by adding barley mash, corn gluten feed and the mixture of barley mash and corn gluten meal. Where, it decreased from 3.01 for the rice grits (base formula) to 1.50, 2.35 and 2.24 for the extrudates containing 30% of barley mash, corn gluten feed and the mixture of barley mash and corn gluten meal, respectively. Barley mash displayed the great reduction in expansion even at low concentration (5%). The undesirable effect on ER may be due to the presence of fiber. These results are in agreement with those obtained by Moore et al. (1990); Lue et al., (1991); Mohi El-Din, (1998) and Yaseen et al., (2001). In this point, Guy (1985) reported that bran particles caused premature rupture of gas cells, which reduced overall expansion. Also, Hsieh et al. (1989 and 1991) found that increasing fiber content increased the axial expansion but decreased the radial expansion. The net results were a decrease in the expansion.

On the other hand, the expansion ratio of the extrudates containing corn gluten meal significantly increased up to 20% substitution. This may be due to the corn gluten expanded more than rice starch. Faubion et al. (1982) reported that addition of soy protein isolate (up to 8%) to wheat starch caused an increase in expansion, whereas similar levels of added wheat gluten caused a reduction in expansion.

Adding 1% of dry skim milk (DSM) to blends containing 10% of the tested materials caused slightly changes in ER of the produced extrudates

(Table, 2).

Table (2). Effect of adding some food industries by products on the physical and functional properties of rice-based extrudates

	phy	sical a	nd function	nal prope	erties o	f rice-	based e	xtrud	ates
Extrudate type		ER	BD	WSI	WAI	BS	Color attributes		
EAG GOOD .	7100		(g/100Cm ³)	%	gg ⁻¹	(Bu)	L*	a*	b*
Rice	grits	3.01 ^a	35.11 ^d	25.48 ^a	8.39 ^a	520°	78.5ª	3.4e	11.0 ^b
(Control)							b	4	
Barley mas	sh,	2.33 ^b	45.03°	10.30 ^b	6.42°	520 ^a	70.6 ^b	6.4 ^d	13.8ª
	5%					h	h	0	10 -3
	10%	2.26 ^{b,c}	49.15 ^b	8.64 ^{b,c}	6.89 ^b	492 ^b	69.4b	7.1°	13.7ª
	20%	2.13d	53.98ª	6.43 ^{c,d}	5.27 ^e	518 ^a	64.1 ^{c,d}	7.8 ^b	14.7ª
	30%	1.50 ^e	54.48°	5.34 ^d	4.86 ^f	509ª	60.4 ^d	8.0ª	14.2ª
10%+1%	DSM	2.22 ^{c,d}	54.16 ^a	8.68 ^{b,c}	5.95 ^d	519ª	68.0 ^{b,c}	7.3°	14.4ª
Rice	grits	3.01 ^b	35.11°	25.48°	8.39ª	520°	78.5 ^a	3.4 ^d	11.0°
(Control)					b	h	ah	- 40	4 = ab
Corn glute	n	3.13ª	34.18 ^d	31.41 ^{a,b}	7.71 ^b	495 ^b	74.5 ^{a,b}	5.1°	15.8 ^b
feed,	5%			h	cd	.=06	70 ob	5.3°	15.7 ^b
	10%	3.03 ^{a,b}	35.87°	30.72 ^b	7.33 ^{c,d}	478°	72.3 ^b	6.2 ^b	17.5°
	20%	2.47°	38.41 ^b	33.35 ^{a,b}	7.04 ^{d,e}	142°	67.8 ^{c,d}		17.5 18.6
	30%		40.94ª	32.62ª,b	6.79 ^e	65 ^f	65.6 ^d	7.0 ^a	
10%+1%	DSM	3.04 ^{a,b}	34.76 ^{c,d}	34.43 ^a	7.51 ^{b,c}	423 ^d	71.1 ^{b,c}	6.6 ^{a,b}	19.2°
Rice	grits	3.01 ^e	35.11ª	25.48 ^b	8.39 ^a	520 ^a	78.5ª	3.4	11.0
(Control)			2 h	3	ob	40 4b	75 50	5.2°	26.3t
Corn g	luten	3.22 ^d	34.14 ^{a,b}	30.12 ^a	7.79 ^b	494 ^b	75.5ª	5.2	20.3
meal,	5%		a b	- 2	0	10=b	70 7b	6.5 ^b	28.8
	10%	-	33.22 ^{a,b}	30.19 ^a	7.12°	485 ^b	70.7 ^b	7.6 ^a	30.8°
	20%		29.26°	26.31 ^b	6.05 ^d	411 ^d	68.2 ^b	8.0 ^a	30.6°
	30%			25.80 ^b	5.33 ^e	232°	66.8 ^b	7.7 ^a	29.4
10%+1%				30.73ª	6.91 ^c	468°	70.8 ^b	3.4 ^e	11.0
Rice	grits	3.01 ^a	35.11 ^{c,d}	25.48 ^a	8.39 ^a	520 ^a	78.5	3.4	11.0
(Control)									
Barley ma		21	hee ee	or oop.c	7.34 ^b	502b	73.5 ^b	5.5 ^d	21.0
Corn glut	en	3.00°	33.23 ^d	21.60 ^{b,c}	7.34	502	13.5	5.5	21.0
meal (1:1)		a ==h	05 04 b.c	24 028.6	6.54°	457°	71.2 ^b	6.8°	23.9
	10%			24.63 ^{a,b}	5.86 ^d	266 ^f			24.3
	20%		36.43 ^{b,c}	21.41°				7.8 ^{a,b}	24.4
	30%		41.31 ^a	9.95 ^d	5.33° 6.67°	424 442 ^d		7.9 ^a	24.2
10%+1%	DSM		37.60 ^{a,b}	26.97ª	0.07	442	/1.4	1.0	27.2

Bu= Brabender unit.

Means having the same letter with each property are not significantly different at $p \le 0.05$.

2.2- Bulk density (BD)

The bulk density (BD) of the extrudates was revealed an opposite trend to that discussed for the ER. If expansion increased, it would be logical to assume the BD would decrease, under the same conditions. Thus, the results in Table (2) indicated that adding barley mash alone or as a mixture with corn gluten meal (1:1) and corn gluten feed increased significantly the BD of the extrudates. The highest increased of BD was noticed in the extrudates containing barley mash, even at low concentration (5%). The high values of BD in extrudates, which contained fiber, may be due to its violent effect on starch gelatinization and on the cell wall also. These results agreed with those esults, which obtained by Moore et al. (1990), Jin et al. (1994), Abd El-Hady et al. (2000) and Yaseen et al. (2001).

On contrary, adding corn gluten meal to produce high protein extrudates cause a significant decrease in BD. Where, the BD decreased from 35.11 g 100 cm⁻³ for base formula to 29.51 g 100 cm⁻³ for that containing 30% corn gluten meal. Meuser and Wiedmann (1989) reported the addition of casein to wheat starch decreased the extrudates bulk density because casein expanded more than wheat starch. While, Martinez-Serna and Villota (1992) observed a 30% decrease in extrusion expansion with the addition of 10%

whey protein isolate to corn starch.

2.3- Water absorption index (WAI) and water solubility index (WSI)

From the same Table (2), it was noticed that WAI significantly decreased by adding all the additives materials. The WAI decreased from 8.39 g water g⁻¹ extrudates in base formula to 4.86, 6.79, 5.33 and 5.33 in the extrudates containing 30% of barley mash, corn gluten feed, corn gluten meal and that contains 30% of the mixture of barley mash and gluten meal (1:1), respectively. These results confirmed those were reported by many investigators such as Berglund et al. (1994), Abd El-Hady et al. (1997, 1999,

2000), Yaseen et al. (2001) and Abd El-Hady (2002).

Regarding the WSI values, it significantly decreased by adding barley mash alone or as a mixture with gluten meal (1: 1). The WSI decreased from 25.48% in the base formula to 5.34 and 9.95% in the extrudates containing 30% barley mash and mixture of barley mash and gluten meal, respectively. As the fiber materials increased, the starchy material contents decreased, causing a reduction in soluble starchy materials (Berglund *et al.*, 1994 and Yaseen *et al.*, 2001). On the other hand, adding corn gluten feed (fiber source) or corn gluten meal (protein source) caused significantly increased in WSI up to 20%, then non-significantly decreased in the extrudates containing 30% from these materials. That is may be because that the composition is different from source to the other (Yaseen *et al.*, 2001). The WSI of the extrudates increased by adding legumes to rice, and the increment was owing to the degradation of starchy materials in blends by extrusion process (Hussein, 1987 and Abd El-Hady *et al.*, 1997).

By adding 1% DSM to blends which containing 10% of the tested

materials, no distinct changes in WSI values were observed.

2.4- Breaking strength (BS)

The data in Table (2) showed that BS of the extrudates significantly decreased by adding both of corn gluten feed and meal. It decreased from 520 Bu for base formula (rice grits) to 65 and 232 Bu in the extrudates

contained 30% gluten feed or meal, respectively. The same observation was noticed in the extrudates containing a mixture of barley mash and gluten meal up to 20% (266 Bu). Adding barley mash alone cause slightly changes in the BS compared with the base formula. Abd El-Hady et al. (1997) reported that the texture of the extruded products is related to the type and quantity of starch, protein materials in products. The BS decreased by adding legumes. This is due to the higher protein content in extrudates comparable with base product. Also, Yaseen et al. (2001) showed that the BS values of the extrudates varied depending on the type and level of fiber in blends.

2.5- Color of the extrudates

The effect of adding used materials on the color properties of rice extrudates is presented in Table (2). A noticed difference of extrudates color was reported. Adding tested materials reduced lightness (L^*) values. This lightness reduction was more pronounced in barley mash (fiber source) enriched extrudates. These results are in agreement with those obtained by

Arora et al. (1993), Jin et al. (1994) and Yaseen et al. (2001).

Comparison among a^* values (degree of redness) of extrudates indicated that extrudates prepared using barley mash and corn gluten meal within the tested range were clearly more red than extrudates prepared using rice grits only. Values of b^* (degree of yellowness) also, increased by adding tested materials. The highest b^* values were observed in the extrudates, which contained corn gluten meal. This due to the high yellow color of the gluten meal. So, the color attributes of the extrudates were influenced by the initial color of the raw materials and extrusion process.

3- Chemical composition of the extrudates

Table (3) shows the chemical composition of extrudates prepared from rice grits with the added materials. It is obvious that, barley mash incorporation significantly increased the moisture content of the extrudates compared with that of base formula. This is may be explained by the fact that fibers tend to retain water in the product. An opposite trend was noticed with other additives. Abd El-Hady et al. (1997) showed that increased legumes in base formula decreased moisture content in the extrudates.

The data showed that, increasing the addition rate of fiber containing materials (barley mash and gluten feed) or protein-containing material (gluten meal) in recipes successively increased the crude fiber and protein contents in the resultant extrudates. The crude fiber content increased from 0.18% for base formula to 3.15, 1.98 and 3.45% for the extrudates containing 30% of barley mash alone or as a mixture with gluten meal and gluten feed, respectively.

The highest increase in protein content was observed in the extrudates containing gluten meal. It increased from 8.02% for base formula to 23.69%

in the extrudate contains 30% corn gluten meal.

With regard to the other components of extrudates samples, variations, depend upon the composition of the ingredients and substitution ratios. Where, the ether extract and ash contents increased with increasing additives. As a result of increasing of protein, crude fiber and other

components contents in the produced extrudates, the carbohydrate contents decreased as shown in Table (3).

Table (3): Effect of adding some food industries by products on the

chemical composition (%) of rice-based extrudates

chem	ical compo	osition (%) of ric				
Extrudate type	Moisture	Total	Protein	Crude	Ether	Ash
-		carbohydrates		fiber	extract	- 0
Rice grit	s 8.7°	89.49 ^a	8.02 ^e	0.18 ^e	1.57°	0.74 ^e
(Control)			4.			
Barley mash, 5%	9.5°	87.19 ^{a.b}	9.52 ^{d.e}	0.61 ^d	1.72°	0.96 ^d
10		84.48 ^b	11.00 ^{c,d}	1.20°	2.10 ^{b.c}	1.22°
20		79.80°	13.70 ^b	2.03 ^b	2.85 ^{a,b}	1.62 ^b
30	% 9.1 ^b	74.93 ^d	16.43°	3.15 ^a	3.62ª	1.87ª
10%+1% DS	M 8.7°	83.86 ^b	11.74°	1.08°	2.03 ^{b,c}	1.29°
Rice gri		89.49 ^a	8.02 ^d	0.18 ^e	1.57ª	0.74°
(Control)				4		
Corn gluten feed	d, 9.1 ^a	87.77 ^{a,b}	8.74°	0.73 ^d	1.69ª	1.07 ^d
5%			h -			4 460
10	% 8.5 ^b	85.90 ^{b.c}	9.61 ^{b,c}	1.29°	1.80ª	1.40°
20		83.16 ^{c,d}	.10.54ªb	2.40 ^b	2.04ª	1.86 ^b
30	% 7.6 ^d	80.20 ^d	11.66°	3.45ª	2.28ª	2.41ª
10%+1% DS	M 8.2°	85.25 ^{b,c}	10.32ª.b	1.21°	1.74ª	1.48°
Rice gri	ts 8.7a	89.49ª	8.02°	0.18ª	1.57°	0.74 ^b
(Control)					b	
Corn gluten me	al, 8.6°	86.79ªb	10.33 ^d	0.27 ^{c,d}	1.78 ^b	0.83 ^{a,t}
5%				h c	ah	
10	% 7.9°	84.06 ^{b.c}	12.62°.d	0.44 ^{b.c}	2.01ª,b	0.87 ^{a,t}
20	% 8.2 ^b	77.55 ^d	18.47 ^b	0.65 ^{a,b}	2.44 ^{a,b}	0.89 ^{a,t}
30	7.5 ^d	71.88°	23.69ª	0.79ª	2.72ª	0.92ª,t
10%+1% DS	8.1 ^{b,c}	83.18 ^c	13.55 ^c	0.38 ^{c,d}	1.94ªb	0.95°
Rice gr	The same of the sa	89.49ª	8.02 ^e	0.18 ^e	1.57°	0.74°
(Control)						
Barley mash +		a.h			· anhr	a ach
Corn gluten me	a! 8.6°	86.32 ^{a,b}	10.33 ^d	0.56 ^d	1.86 ^{b.c}	0.93 ^b
	%	d		0.000	0.4=00	4 000
10	0% 8.3 ^b	83.78 ^d	12.12°	0.87°	2.17 ^{b,c}	1.06
20	0% 8.3 ^b	78.13°	16.82 ^b	1.39 ^b	2.56 ^{a,b}	1.10
30	6.0 ^d	72.23 ^d	21.30 ^a	1.98°	3.16ª	1.33
10%+1% DS	8.0°	83.02 ^b	12.97°	0.79 ^{c,d}	2.10 ^{b.c}	1.12

Means of triplicates

Calculated by difference

Means having the same letter with each property are not significantly different at $p \le 0.05$.

4- Minerals content

The contents of K, Ca, Mg. Fe, Mn and Zn of the extrudates are presented in Table (4). The results showed that the addition of the tested materials increased the contents of the determine minerals of the extrudates. The main increases were occurred in potassium, magnesium and calcium contents. The greatest increment in potassium and magnesium contents was observed in the extrudates containing corn gluten feed, which rich in these

minerals (Schroeder, 1999). Where, it increased from 159.3 and 21.00 mg/ 100 g in base formula to 609.31 and 171.00 mg/ 100 g in extrudates containing 30% corn gluten feed. Barley mash displayed the highest increment in Calcium, Zinc and Ferric contents. The increments in determined minerals were low in the extrudates containing gluten meal because it has low ash content (1.30%) compared with other additives, as shown in Table (1). Adding 1% DSM to the extrudates contain 10% of additives materials caused increase in all determined minerals. The main increment was observed in Calcium content.

Table (4): Effect of adding some food industries by products on some minerals contents (mg 100 g⁻¹) of rice-based extrudates

minerals contents			(mg ivu	9 101	ice-pas			
Extrudate type			K	Ca	Mg	Fe	Mn	Zn
Rice grits (Control)		159.30°	51.00°	21.00	5.75°	0.60 ^d	1.08°
Barley mash,	,	5%	187.02 ^d	88.00 ^d	61.61 ^e	6.74 ^d	0.70°.d	1.48 ^d
barrey masn,		10%	197.12°	92.00°	66.30 ^d	8.58°	0.89°	1.65 ^d
			207.73 ^b	94.61°	94.13 ^b	15.28b	1.40 ^b	2.55 ^b
			207.92 ^b	152.49 ^a	110.01ª	19.36°	1.88ª	2.97ª
	10%+1%		228.92ª	105.20 ^b	86.19°	8.98°	1.08°	1.86°
Rice grits (Contro			159.30 ¹	51.00 ^d	21.00	5.75ª	0.60°	1.08°
Corn gluten feed,	.,	5%	275.03°	70.35°	84.20°	2.94d	0.65 ^b	1.36 ^d
oom graten reed,		10%	346.45 ^d	71.51°	100.55 ^d	3.06°	0.69 ^{a,b}	1.55°
		20%	555.80 ^b	72.98°	156.01 ^b	3.47 ^{b.c}	0.78ab	1.86ª.t
		30%	609.31 ^a	99.67ª	171.00°	3.86 ^b	0.78 ^{a,b}	1.93°
	10%+1%		364.71°	95.08 ^b	122.88°	3.27°	0.89ª	1.70 ^{b.0}
Rice grits (Contro			159.30 ^d	51.00 ^d	21.00°	5.75°	0.60 ^{a,b}	1.08ª
Corn gluten meal		5%	193.65°	83.24°	22.88e	3.24°	0.49 ^b	0.95°
Com grater mean		10%	203.04 ^b	84.87 ^{b.c}	28.23 ^d	3.91 ^b	0.59a,b	0.98ª
		20%	206.97 ^b	87.15 ^b	35.01°	4.36 ^b	0.68 ^{a,b}	1.05 ^a
		30%	285.95°	92.29ª	43.24ª	4.38 ^b	0.76°	1.15°
	10%+1%		208.92 ^b	93.00°	40.26b	4.13 ^b	0.66a,b	1.11 ^a
Rice grits (Contro			159.30°	51.00	21.00°	5.75°	0.60 ^d	1.08
Barley mash + Co	orn gluten	meal 5%	188.18°	80.70°	48.91 ^d	5.03 ^f	0.69°	1.12
(1:1),		10%	199.56 ^b	85.11 ^d	55.62°	6.76°	0.69°	1.37
			202.84 ^{a.b}		57.99°			1.85
		30%	207.61 ²	103.94°			1.28ª	2.32
	10%+1%	DSM	203.19ªb				0.88 ^{b.c}	1.50
	10 70 . 1 70	00111	200.10	100.00				

Calculated on dry basis

Means having the same letter with each property are not significantly different at p \leq 0.05.

5- Sensory properties of produced extrudates

The organoleptic properties remains the final judge of food quality. Thus, the effect of adding tested materials was evaluated through sensory evaluation individually with rice base extrudate.

The results of sensory evaluation of rice extrudates with tested materials are presented in Table (5). The high scores were noticed in taste of extrudate samples, which prepared from rice grits (15.0 degree) and that containing 5% of barley mash either alone (15.0) or as a mixture with gluten meal (16.0), 10% of both corn gluten feed (15.83) and meal (17.0).

Overall acceptability Excellent Good Poor Fair Fair Fair Fair Fair Fair Table (5). Effect of adding some food industries by products on the sensory properties of rice-based extrudates 80.30a,b,c 81.34^{a,b} 78.33a,b 79.42^{a,b} 77.71^{a,b} 75.01^{b,c} 80.42ª.b 78.40a.b 72.01^b 82.15^a 43.33d 74.39° 83.43ª 82.86ª 85.85ª 78.60ª 64.83° 83.72ª 74.39^b 84.43ª 67.88° 81.77ª 74.39^b distribution 7.20a,b 7.718 6.50^b 7.88ª 6.86^b 4.17° 8.14ª 7.88ª 8.14ª 7.67a 7.88ª 8.33ª 8.17a 8.57a 7.57a 7.43ª 7.33ª 7.86ª 6.86^b 8.00a 7.86ª 7.88ª 7.75a 8.13ª characteristics Surface 7.40a,b 7.50a.b 7.29^{b,c} 7.38^{b,c} 8.29a.b 8.33a,b 7.83b.c 7.43°,d 7.71ª,b 7.57a.b 3.839 7.71ª 6.50° 7.00^d 8.71a 7.86ª 6.83° 8.14ª 6.88° 7.00° 8.00ª 7.00° 8.00a 6.50a.b 8.00a,b 7.57a.b 7.86ab 8.41ª 7.17ª Color 6.86ª 3.83 7.67ª 7.86ª 7.71ª 7.33^b 6.88^b 5.50° 7.63ª 7.20a 7.29ª 7.50ª 6.43b 7.86ª 6.00° 6.00° 6.00° Chewiness 12.67ª 10.75^b 13.43ª 12.71ª 13.38ª 10.50ª 11.00ª 12.29^a 11.33 10.50^b 13.29ª 13.00ª 12.29ª 12.86ª 10.50^b 13.00ª 12.71ª 13.00a 12.17^a 13.14ª 12.75ª 10.50^b 8.67^b 6.67° 3.43ª 13.25a 2.86ª 11.50ª 12.67a 12.29ª 12.33ª 12.00a 11.14ª 2.86ª 3.00a 12.86ª 12.17ª 12.57a 12.57a 12.63ª 11.00ª 14.20° 12.83 12.88ª 12.88ª 12.57ª Odor 12.88ª Crispness 16.29^{a,b} 15.71^{a,b} 16.57^{a,b} 15.71^b 16.83ª 16.88ª 16.75ª 15.13^{6,6} 13.75 15.13^b 13.00° 15.13^b 17.33ª 17.57ª 17.57ª 15.13^b 17.43ª 17.29a 17.86ª 17.83ª 17.43 9.83_d 16.6ª 4.00° 13.88^{b.c} 16.71^{a,b} 10%+1% DSM 14.63ª.b 10% 14.43ª.b 13.67ª 15.00^{a,b} Taste 15.00ª 5.00a 14.57ª 13.00ª 15.00^a 14.71ª 5.83ª 15.67ª 13.29ª 15.29ª 15.00^b 17.00^a 17.00a 14.67^b 17.29ª 16.00ª 12.25° 9.33^b 20% 20% 30% meal, 10% 30% 20% 10% 20% 30% 10% 30% 10%+1% DSM 10%+1% DSM 10%+1% DSM Corn gluten feed, 5% gluten meal (1:1), 5% Rice grits (Control) Rice grits (Control) Barley mash + corn Rice grits (Control) Rice grits (Control) Extrudate type gluten Barley mash, Corn 2%

Means having the same letter with each property are not significantly different at p ≤ 0.05

6910

The mean scores significantly decreased by increasing the ratio of additives materials in its blends. Extrudates containing corn gluten meal had highest taste scores at different ratios compared with other materials. As shown in the same Table, it could be noticed that, the tested materials had no significant effect under all tested levels on the odor of produced extrudates.

The data presented in Table (5) show that adding barley mash alone or as a mixture with corn gluten meal up to 10% increased the crispness, color, surface characteristics and pore distribution scores of the resultant extrudates. By increasing the addition levels from these materials in blends, the mean scores of these properties decreased. Extrudates prepared with corn gluten feed or meal at any level of addition received high crispness scores compared with those for base formula. Adding gluten feed or meal up to 20% enhanced the color, surface characteristics and pore distribution of the resultant extrudates. Many authors reported that, attempts to incorporate high levels of fiber in extruded product often resulted in compact, non-crisp, tough and undesirable texture in extrudates (Anderson et al., 1981 and Hu-L, 1994). Also, Skierkowshi et al. (1990) reported that crispness scores were highest in blends containing 13-16% protein content. At values below or above this range of protein, the scores decreased and indicated that the extrudates would not be acceptable to consumers.

Generally, from the data in Table (5), it can observed that, addition of tested materials up to 10% in replacement of rice grits significantly improved almost the tested properties of the product resulting overall acceptability with good grade in comparison with control sample which scores a fair grade (74.39%). By increasing the replacement from 10% to 30%, the calculated scores were decreased, but the final grade still good in the extrudates containing corn gluten feed or meal. But, those containing barley mash either alone or as a mixture with gluten meal the grade decreased to poor (43.33%)

and fair (67.88%), respectively.

Finally, it could be concluded from this subjective evaluation that high fiber, high protein extrudates with acceptable quality could be prepared from barley mash alone or as a mixture with gluten meal, corn gluten feed or meal up to 10%. Addition of 1% DSM enhanced the overall acceptability of the extrudates, especially which containing gluten meal (excellent grade).

REFERENCES

A.O.A.C. (1995). Association of Official Analytical Chemists. Official Methods of Analysis. 16th Ed. Association of Official Analytical Chemists, Washington, DC, USA.

Abbott, P. (1987). Coextrusion: Recent developments using cooking-

extruders. Cereal Foods World, 32: 816.

Abd El-Hady, E. A. (2002). Amaranth meal as a protein and essential amino acids supplement in some extrudates, cookies and macaroni. Arab Univ. J. Agric. Sci., Ain Shams Univ., Cairo, 10 (2): 707-724.

Abd El-Hady, E. A. and R. A. Habiba (2003). Effect of soaking and extrusion conditions on antinutrients and protein digestibility of legume seeds. Lebensm.-Wiss. U.- Technol.. 36: 285-293.

Abd El-Hady, E. A.; G. A. Mostafa and S. K. El-Samahy (1997). Production of rice extrudates with high nutritional value. Egypt. J. Appl. Sci., 12: 172-

Abd El-Hady, E. A.; G. A. Mostafa; S. K. El-Samahy and I. A. El-Saies (1999). :1-Maisextrudate angereicherter Herstellung Proteinananreicherung (Production of enriched corn extrudates. II-Protein enrichment). Getreide Mehl und Brot, 53 (6): 368-378.

Abd El-Hady, E. A.; G. A. Mostafa; S. K. El-Samahy and I. A. El-Saies (2000). .2-Maisextrudate angereicherter Ballaststoffanreicherung (Production of enriched corn extrudates. II.

Fiber enrichment). Getreide Mehl und Brot, 54 (3): 195-200.

Abd El-Hady, E. A.; S. K. El-Samahy; G. A. Mostafa and K. M. Youssef (2002). Einsatz von Dattepulpe und-konzentrat in Reisextrudaten. (Use of date pulp and concentrate in rice based extrudates). Getreide Mehl und Brot, 56 (3): 179-185.

Almeida-Dominguez, N. G.; M. E. Valencia and I. Higuera-Ciapara (1990). Formulation of corn-based snacks with high nutritive value: biological

and sensory evaluation. J. Food Sci., 55 (1): 228-231.

Anderson, R. A.; H. F. Conway; V. F. Pfeifer and E. L. Griffin Jr (1969). Gelatinization of corn grits by roll- and extrusion-cooking. Cereal Sci. Today, 14: 4-7.

Andersson, Y.; B. Hedlund; L. Jonsson and S. Svesson (1981). Extrusion cooking of a high-fiber cereal product with crispbread character. Cereal

Chem., 58: 370-374.

Arora, A.; J. Zhao and M. E. Camire (1993). Extruded potato peels functional properties affected by extrusion conditions. J. Food Sci., 58 (2): 335-

Berglund, P. T.; C. F. Fastnaugh and E. T. Holm (1994). Physico-chemical and sensory evaluation of extruded high fiber barley cereals. Cereal

Chem., 71 (1): 91-95.

Bjorck, I.; M. Nyman and N. G. Asp (1984). Extrusion cooking and dietary fiber: Effects on dietary fiber content and on degradation in the rat intestinal tract. Cereal Chem., 61: 174-179.

Bollinger, H. (1996). Wheat fiber- a new generation of dietary fibers. Food

Tech. Europe, 3 (3): 34, 36, 38.

Colonna, P.; J. Tayeb and C. Mercier (1989). Extrusion cooking of starch and starchy products. pp. 247-319, In "Extrusion-Cooking" Mercier, C.; P. Linko and J. M. Harper, eds. Am. Assoc. Cereal Chem., St. Paul, MN.

Cottenie, A.; Verloo, A.; Kiekense, L.; Velghe, G. and Camerynck, L. (1982). Chemical Analysis of Plant and Soil. State Univ.of Belgium-Gent, Hand Book, Belgium. 1-6.

Dziezak, J. D. (1989). Single and Twin-screw extruders in food processing.

Food Eng., 43: 164.

Faubion, J. M.; R. C. Hoseney and P. A. Seib (1982). Functionality of grain components in extrusion. Cereal Foods World, 27: 212-216.

- Gomez, M. H. and J. M. Aguilera (1984). A physico-chemical model for extrusion of corn starch. J. Food Sci., 49: 40-43, 63.
- Gordon, D. T. (1989). Functional properties vs. Physilogical action of total dietary fiber. Cereal Food World, 34: 517.
- Guy, R. C. F. (1985). The extrusion revolution. Food Manufacture, January:26.
- Hakulin, S.; Y. Y. Linko; P. Linko; K. Seiler and W. S. Detmold (1983). Enzymatic conversion of starch in twin-screw HTST-extruder. Starch/ Staerke, 35: 411.
- Hsieh, F.; H. E. Huff; S. Lue and L. Stringer (1991). Twin-screw extrusion of sugar beet fiber and corn meal. Lebensm. Wiss. Technol., 24: 495-500.
- Hsieh, F.; S. J. Mulvaney; H. E. Huff; S. Lue and J. JR. Brent (1989). Effects of dietary fiber and screw speed on some extrusion processing and product variables. Lebensm. Wiss. Technol., 22: 204-207.
- Hu-L. (1994). Food emulsifier effects on corn meal extrusion with dietary fiber, salt and sugar. Cereal Chem., 71 (3): 227-237.
- Hussein, M. H. (1987). Production and evaluation of baby food mixtures from some raw and extruded starch and proteinaceous materials. Ph.D. Thesis, Fac. of Agric., Cairo Univ., Egypt.
- Jin, Z.; F. Hsieh and H. E. Huff (1994). Extrusion cooking of corn meal with soy fiber, salt and sugar. Cereal Chem. 71:227-234.
- Kee, H. J.; G. H. Ryu and Y. K. Park (2001). Physical properties of extruded snack made of dried onion and onion pomace. J. Korean Soc. Food Sci. Nutr., 30(1): 64-69.
- Konstance, R. P.; C. I. Onwulata; P. W. Smith; D. Lu; M. H. Tunick; E. D. Strange and V. H. Holsinger (1998). Nutrient-based corn and soy products by twin-screw extrusion. J. Food Sci., 63 (5): 864-868.
- Kramer, A. and B. A. Twigg (1970). Quality Control for the Food Industry. 3rd edition, Volume 1 pp.120-154. Fundamentals, the AVI Publishing Co., Inc., USA.
- Linko, P.; P. Colonna and C. Mercier (1981). High temperature short time extrusion cooking. Advances in Cereal Sci. Technol., 4: 145-235.
- Lue, S.; F. Hsieh and H. E. Huff (1991). Extrusion cooking of corn meal and sugar beet fiber Effect of expansion properties, starch gelatinisation and dietary fiber content. Cereal Chem., 68 (3): 227-234.
- Martinez-Serna, M. D. and R. Villota (1992). Reactivity, functionality, and extrusion performance of native and chemically modified whey protein. In "Food Extrusion Science and Technology". J. L. Kokini, C. T. Ho and M. V. Karwe, eds. Mercel Dekker, New York, USA.
- Meuser, F. and W. Wiedmann (1989). Extrusion plant design. Pages 128-133 in Extrusion Cooking. C. Mercier, P. Linko and J. M. Harper, eds. Am. Assoc. Cereal Chem., St. Paul. MN.
- Mohi El-Din, F. B. A. (1998). Studies on production and evaluation of some low calorie foods. M.Sc. Thesis, Fac. of Agric., Cairo Univ., Egypt.
- Moore, D.; E. Sanei; Z. Vanhecke and J. M. Bouvier (1990). Effect of ingredients on physical/ structural properties of extrudate. J. Food Sci., 55: 1383-1387, 1402.

Murphy, M. G.; D. I. Skongberg; M. E. Camire; M. P. Dougherty; R. C. Bayer and J. L. Briggs (2003). Chemical composition and physical properties of extruded snacks containing crab-processing by-product. J. Sci. Food Agric., 83: 1163-1167.

Obatolu, V. A.; D. I. Skonberg; M. E. Camire and M. P. Dougherty (2005). Effect of moisture content and screw speed on the physical chemical properties of an extruded crab-based snack. Food Sci. Technol. Inter.,

Ott, L. (1984). An Introduction to Statistical Methods and Date Analysis. 2nd

edition, PWS publisher, Boston, M. A., USA.

Rhee, K. S.; S. H. Cho and A. M. Pradahn (1999). Expanded extrudates from corn starch-lamb blends: process optimization using response surface methodology. Meat Sci., 52: 127-134.

Roseg, D.; I. Filipi and T. Petrak (1991). Extrusion of protein- rich animal by-

products. Tehnologija-Mesa, 32 (2): 74-76.

Saleh, H. S. (1996). Production and evaluation of extrudates from yellow corn grits blends. M.Sc. Thesis, Fac. of Agric., Cairo Univ., Egypt.

Schroeder, J. W. (1999). By-Products and Regionally Available Alternative Feedstuffs for Dairy Cattle. AS-1180.NDSU Extension Service, North Dakota State Univ., USA.

Singh, D.; G. S. Chauhan; S. M. Tyagi and I. Suresh (2000). Extruded snacks from composite of rice brokens and wheat bran. J. Food Sci. Technol.,

India. 37 (1): 1-5.

Skierkowski, K.; E. Gujska and K. Khan (1990). Instrumental and sensory evaluation of textural properties of extrudates from blends of high starch/ high protein fractions of dry beans. J. Food Sci., 55 (4): 1084-

Stauffer, C. E. (1993). Dietary fiber analysis, physiology and calori reduction. In "Advances in Baking Technology", B. S. Kamel and C. E. Stauffer

(eds), pp. 371-384. published by VHC, Inc., New York, NY.

Yaseen, A. A. E.; A. A. Shouk and E. A. Abd El-Hady (2001). High fiber extrudate as affected by fiber source and hydrocolloids. J. Agric. Sci. Mansoura Univ., 26 (2): 943-960.

الاستفادة من المنتجات الثانوية لبعض الصناعات الغذائية في انتاج مبثوقات الأرز عالية المحتوى من الألياف والبروتين

سوسن يوسف الفحام ، عادل أبو بكر شطا " و خالد محمد يوسف "

قسم الصناعات الغذائية، المركز القومي للبحوث، الدقي، الجيزة، ج.م.ع.

" قسم الصناعات الغذائية، كلية الزراعة، جامعة قناة السويس، الاسماعيلية، ج.م.ع.

استهدفت هذه الدراسة امكانية استخدام ثلاث منتجات ثانوية هي مخلف الشعير المنبت والناتج خلال تصنيع البيرة، الجلوتين فيد Gluten feed والجلوتين ميل Gluten meal والجلوتين ميل Gluten feed الناتجان خلال تصنيع نشا الذرة في انتاج مبثوقات الأرز عالية المحتوى من الألياف والبروتين بهدف تعظيم الاستفادة من هذه المنتجات الثانوية. تميز كل من مخلف الشعير والجلوتين فيد بارتفاع محتواهما من الألياف (13,01 و 11,78% علي الترتيب) والرماد (7,70% و 73,67% علي الترتيب)، بينما تميز الجلوتين ميل بارتفاع محتواه من البروتين (70,00%). اضيفت هذه المواد منقودة أو مخلوط من مخلف الشعير والجلوتين ميل (11)فقط بنسب م، ١٠، ٢٠ و ٣٠% لرفع محتوى المبثوقات الناتجة من الالياف والبروتين. تم دراسة تأثير هذه الاضافات على كل من الخواص الطبيعية والوظيفية (نسبة التمدد، الكثافة، معامل امتصاص الماء، معامل درجة الذوبان في الماء، قوة الكسر، اللون)، التركيب الكيماوي، المحتوي من بعض العناصر المعدنية و أخير الخصائص الحسية للمنتج النهائي.

أوضحت النتائج المتحصل عليها أن اضافة مخلف الشعير منفردا أو كمحلوط بنسبة 1:1 مع الجلوتين ميل Gluten feed وكذا الجلوتين فيد Gluten meal وكذا الجلوتين فيد الماء، قوة الكسر وقيم L^* في من نسبة التمدد، معامل امتصاص الماء، معامل درجة الذوبان في الماء، قوة الكسر وقيم L^* في المنتجات، بينما أزدادت قيم كثافتها. أدت اضافة الجلوتين ميل Gluten meal منفردا الي زيادة في نسب التمدد وقيم L^* المنتجات. اختلف التركيب الكيماوي ومحتوي المنتجات من بعض العناصر المعدنية تبعا لنوع ونسب المواد المضافة.

أوضح التقييم الحسي امكانية انتاج مبثوقات أرز غنية بالألياف والبروتين ومقبولة حسيا باستخدام المواد المختبرة حتى نسبة اضافة ١٠% فقط.

